



Ovation H-265WW

Ovation H-265WW is a silent, convection cooled LED houselight with a powerful warm white light output and a high CRI, ideal for theatres, worship venues and recital halls or any other application where silent operation is crucial. The unit also features 16-bit dimming, RDM and W-DMX control as well as adjustable PWM to prevent flickering on televised performances. Interchangeable lenses for height adjustment are another indispensable feature in theatrical and house of worship applications. For even more versatility, the yoke can be completely removed, and the fixture suspended, pendant style, from a loop on the back plate. Available in black or white.



At a Glance

- High-power warm white, convection cooled houselight
- Interchangeable lens plates to adapt to different mounting heights
- 5-pin XLR and terminal blocks for DMX connections
- Use included yoke for mounting, or suspend from integrated loop-eye
- 16-bit dimming for ultra-smooth fades
- DMX, WDMX and RDM (Remote Device Management) for added programming flexibility
- Adjustable PWM (Pulse Width Modulation) to avoid flickering on camera

Specifications

Optical

- Light Source: 1 LEDs (WW) 230 W, (2.3 A), 3258 K, 50,000 hours life expectancy
- Color Temperature (at full): 3258 K
- CRI: 97
- Beam Angle (w/80° filter): 40°
- Beam Angle (w/65°): 50°
- Beam Angle (w/45° lens): 39°
- Beam Angle (w/25° lens): 19°
- Field Angle (w/65°): 79°
- Field Angle (w/45° lens): 69°
- Field Angle (w/25° lens): 36°
- Lumens (w/80° filter): 7,912
- Lumens (w/65° lens): 8,505
- Lumens (w/45° lens): 8,885
- Lumens (w/25° lens): 9,139
- Illuminance (w/80° filter) : 325 lux @ 5 m
- Illuminance (w/65°): 400 lux @ 5 m
- Illuminance (w/45° lens): 623 lux @ 5 m
- Illuminance (w/25° lens): 1,933 lux @ 5 m
- Selectable PWM: 600Hz, 1,200Hz, 2,000Hz, 4,000Hz, 6,000Hz, 25 kHz

Construction / Physical

- Dimensions: 13.11 x 9.44 x 13.34 in (333 x 240 x 339 mm)
- Weight: 17.8 lb (8.1 kg)
- Exterior Color: White

Control

- Control Protocol: DMX, W-DMX, RDM
- DMX Channels: 1, 2, 3 or 6
- Modes/Personalities: 4 personalities (1CH, 2CH, 3CH, 6CH)

Certifications / Qualifications

- CE, MET, FCC
- IP Rating: IP20, dry location
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Dynamic Effects

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 30 Hz
- Dim Modes: 4
- Built-in Automated Programs: Yes

Connections

- Power Connection: Bare-wired
- Power Input: Hard-wired
- Data Connectors: 5-pin XLR, Phoenix connector
- Cable Length (power): 15 ft (4.5 m)

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 147 W, 1.21 A @ 120 V, 60 Hz
- Power and Current: 147 W, .694 A @ 208 V, 60 Hz
- Power and Current: 149 W, .641 A @ 230 V, 50 Hz
- Breaker Size: T3.15 A, 250 V

What's Included

- Ovation H-265WW
- 65°, 45° and 25° Lenses
- 80° Filter
- Egg Crate

Optional Accessories

- Ovation H-265WW
- Professional Clamps: CTC-50HC, CTC-50HCN
- 5-pin DMX Cables
- Ovation H-265WW

Ordering Info

- Item Code: 03031466