



✉ info@lemark.co.uk

☎ (UK) 01480 494540  
(Int.) +44 1480 494540

🌐 www.lemark.co.uk

Le Mark Group Ltd., 1 Houghton Hill Ind., Sawtry Way,  
Houghton, Cambridgeshire, PE28 2DH England

Registered in England 1761971 VAT No. GB 395772693



## Harmony Fresh

Technical Parameter	Standard	Unit	Result
Construction			Heterogeneous
Total thickness	mm	EN 428	2.0
Wear layer thickness	mm	EN 429	0.35
Length of rolls	lm	EN 426	25
Width	m	EN 426	2
Total Weight	Kg/m <sup>2</sup>	EN 430	1.3
Residual Indentation	Max.mm	EN 433	0.2
Dimensional Stability	Max. %	EN 434	±0.2
Curling	Max.mm	MSZ EN 434	8
Fire Resistance	class	EN 13501-1	Cfl-s1
	class	DIN 4102/ÖNORM	B1
Abrasion Group	Group	MSZ EN 660-1	T
Abrasion Resistance	Max.m	MSZ EN 423	<250
Light Fastness	Grade	EN 20105 B02	> 6
Chemical resistance		EN 423	no change
Slip Resistance	class	EN 13893	DS
Castor Chair Resistance		EN 425	no change
Flexibility (diameter 20/40mm)	Visual evaluation	MSZ EN 435	no change
Surface Treatment			CLP
Antibacterial and Fungicid treatment			
Environmental attributes			Solvent and heavy metal free product
CE MARKING	EN14041		✓

TAPES

LABELS

FLOORS

CREW WEAR

### **Important notices**

The above figures are average values and should not be regarded as maximum or minimum values.

### **Storage**

This item should be stored at room temperature, away from direct sunlight and damp.

Version Number: 1

Last revision date: 07/10/24

TAPES

LABELS

FLOORS

CREW WEAR